Miele PROFESSIONAL

PROFESSIONAL WASHING MACHINE
PW 6065 VARIO

- Drum volume 59 l, load capacity 6.5 kg
- Wide variety of programmes – special disinfection programme
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient – low water and energy consumption
- Perfect spinning results – residual moisture 47 %*, g-factor526

EAN : 4002514257563 / Article no. : 51606504AUS / Mat. no. : 06943580

Construction type and version	
Construction type	Front-loader, stackable
Range	Professional - Little Giants
Front	Stainless steel
Load ratio	1:9
Load in kg	6.5
Drum volume in l	59
Door opening [Ø] in mm	300
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Patented honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for fast food restaurants	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for domestic use	•
Suitable for doctors' and dentists' practices	•
Performance data	
Programme duration in minutes with cold water connection	59
Programme duration in minutes with cold water and hot water connection	49
Residual moisture with cold rinse in %	49
Residual moisture with hot rinse in %	47
Spin speed in rpm	1,400
g factor	526
Tested operating hours	30,000
Controls	
Control system	Profitronic L Vario
Programmability	programmable
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Patented AutoClean detergent drawer	•
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•

Miele PROFESSIONAL

PROFESSIONAL WASHING MACHINE
PW 6065 VARIO

Standard electrical connection	
Heating type	Electrical
Electrical connection	220-240V~ 50HZ
Heater rating in kW	4,75-5,70
Total connected load in kW	5,05-6,00
Fuse rating in A	25
Water connection/drainage	
Cold water [number]	1x 1/2" mit 3/4" Verschraubung
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Grey water (optional) [number]	1x 1/2" with 3/4" threaded union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	850
External dimensions, width in mm	595
External dimensions, depth in mm	725
Net weight in kg	109
Maximum floor loading in N	3000
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.00
Features	
Imbalance monitoring	•
Disinfection rinse	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
LED drum lighting, class 1	•
Communication slot (optional)	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak load cut-out/energy management (optional)	•
Test certificate	
Splash-proof safety rating IPX4	•
WEEE	•
RCM	•
Complies with Machinery Directive 2006/42/EC	•